

HOSHIZAKI




- 1. Install the product properly in accordance with the instructions on location, electrical connections stated in the instruction manual provided. Allow 10mm extra space at the installation site to meet any installation requirements(additional spacing is also required for proper air flow and pipe connections).
- 2. The heat rejection is based on the reached pulldown temperature at ambient temperature of 32° C and power supply of 230V 50Hz.


 The amperage and electric consumption are based on measurements at ambient temperature of 38° C and power supply of 230V 50Hz.
- 3. The cabinet temperature range of -25 to -7° C is guaranteed at ambient temperature of 38° C.


 4. Product code:T014-D102



ITEM	Hoshizaki Drawer Type Undercounter Refrigerator
MODEL	FTC-167DNA
POWER SUPPLY	1 Phase 230V 50Hz Capacity:0.54kVA(2.5A)
AMPERAGE	Rated:3.6A
ELECTRIC CONSUMPTION	Heater:398W Defrost:330W
HEAT REJECTION	*W
POWER CORD	2.0m (UK Plug with Earth Wire)
EFFECTIVE CAPACITY	324L
OUTSIDE DIMENSIONS	1670mm(W)x600mm(D)x850mm(H) (850-880)mm
INSIDE DIMENSIONS	1300mm(W)x433mm(D)x588mm(H)
EXTERIOR	Stainless Steel, Galvanized Steel (Rear/Bottom)
INTERIOR	Stainless Steel, ABS Plastic
INSULATION	Polyurethane Foam
INSULATION FOAM BLOWING AGENT	Cyclopentane
REFRIGERATION SYSTEM	Forced Air Circulation
DEFROST SYSTEM	Heater
COMPRESSOR	Hermetic
CONDENSER	Fin and Tube type, Air—cooled
EVAPORATOR	Fin and Tube Type
REFRIGERANT	R404A/190g
TEMPERATURE CONTROL	Microprocessor (Digital Temp Indication) Adjustable from -25 to-7°C
DEFROST CONTROL	Microprocessor
ELECTRIC CIRCUIT PROTECTION	Fuse, Earth Wire
REFRIGERANT CIRCUIT PROTECTION	Motor Protector
LEG	Plastic Adjustable 150 to 180mm
WEIGHT	164kg (Gross Approx. *kg)
PACKAGE	Carton 1735mm(W)x680mm(D)x790mm(H)
ACCESSORIES	7,
OPERATING CONDITIONS	Ambient Temperature:5-38° C Voltage Range:Rated Voltage±6%
*We reserve the right t	o make changes in specifications and design without prior notice.







	APPROVED CHECKED TORIHATA LIU * *			DESIGNED ZHOU	DRAWN ZHOU		SCALE -	1/	[/] 20	TRIGONOMETRY	
*			Δ	****		DATE	7 40 4	_	DRAWING NO	0 - 0	SYMBOL
APPROVED	ROVED DESIGNED		SYMBOL	DATE		202.	5.12.1.	5	D5/	658	/-\