



ITEM	Hoshizaki Undercounter Refrigerator
MODEL	RT-188MA-P-PRS
POWER SUPPLY	1 Phase 230V 60Hz Capacity: 0.78kVA (3.55A)
AMPERAGE	Rated 2.5A
ELECTRIC CONSUMPTION	Heater 149W
HEAT REJECTION	*W
POWER CORD	2.0m (Plug with Earth Wire)
EFFECTIVE CAPACITY	517L
OUTSIDE DIMENSIONS	1800mm (W) x750mm (D) x1076(-1106)mm (H)
INSIDE DIMENSIONS	1440mm (W) x 586mm (D) x 599mm (H)
EXTERIOR	Stainless Steel, Galvanized Steel (Rear / Bottom) ABS Plastic (Top & Bottom on Door)
INTERIOR	Stainless Steel
INSULATION	Polyurethane Foam
INSULATION FOAM BLOWING AGENT	Cyclopentane
REFRIGERATION SYSTEM	Forced Air Circulation
DEFROST SYSTEM	Off Cycle
COMPRESSOR	Hermetic
CONDENSER	Fin and Tube type, Air-cooled
EVAPORATOR	Fin and Tube Type
REFRIGERANT	R134a
TEMPERATURE CONTROL	Microprocessor controlled Adjustable from -6 to 12°C
DEFROST CONTROL	Microprocessor controlled
ELECTRIC CIRCUIT PROTECTION	Fuse, Earth Wire
COMPRESSOR PROTECTION	Motor Protector
LEG	Plastic Adjustable 150 to 180mm
SHELF	6pcs.
WEIGHT	Net:108kg (Gross: Approx. 113kg)
PACKAGE	Carton 1865mm (W) x830mm (D) x1025mm (H)
ACCESSORIES	Drain Hose x 1, Drain Pan x 1
OPERATING CONDITIONS	Ambient Temperature: 5-38°C Voltage Range: Rated Voltage±6%

*CUSTOMIZED
TOP PANEL OPENING
(GN PAN SIZE: 1/3×9×1; COVER+CUTTING BOARD)

APPROVED TORIHATA	CHECKED ZHOU	DESIGNED ZHOU	DRAWN ZHOU	SCALE 1/30	TRIGONOMETRY		
*	*	△	****	DATE 2024.1.18	DRAWING NO. D37886	SYMBOL △	
APPROVED	DESIGNED	SYMBOL	DATE				