



HOSHIZAKI














ITEM	Hoshizaki Undercounter Refrigerator					
MODEL	RT-188MA-SG					
POWER SUPPLY	1 Phase 230V 50Hz Capacity: 0.5kVA (2.5A)					
AMPERAGE	Rated 2.5A					
ELECTRIC CONSUMPTION	Heater 264W Defrost 165W					
HEAT REJECTION	*W					
POWER CORD	2.0m (UK Plug with Earth Wire)					
EFFECTIVE CAPACITY	502L					
OUTSIDE DIMENSIONS	1800mm (W) x 750mm (D) x 850(-880)mm (H)					
INSIDE DIMENSIONS	1440mm (W) x 586mm (D) x 599mm (H)					
EXTERIOR	Stainless Steel, Galvanized Steel (Rear / Bottom) Double Layer Glass with Heat Reflection Film(Glass Door)					
INTERIOR	Stainless Steel					
INSULATION	Polyurethane Foam					
INSULATION FOAM BLOWING AGENT	Cyclopentane					
REFRIGERATION SYSTEM	Forced Air Circulation					
DEFROST SYSTEM	Glass Tube Heater					
COMPRESSOR	Hermetic					
CONDENSER	Wire and Tube type, Air—cooled					
EVAPORATOR	Fin and Tube Type					
REFRIGERANT	R134a					
TEMPERATURE CONTROL	Microprocessor controlled Adjustable from -2 to 12°C					
DEFROST CONTROL	Microprocessor controlled					
ELECTRIC CIRCUIT PROTECTION	Fuse, Earth Wire					
COMPRESSOR PROTECTION	Motor Protector					
LEG	Plastic Adjustable 150 to 180mm					
SHELF	6pcs.					
WEIGHT	Net:122kg (Gross: Approx. 137kg)					
PACKAGE	Carton 1865mm (W) x 830mm (D) x 790mm (H)					
ACCESSORIES	_					
OPERATING CONDITIONS	Ambient Temperature: 5-38°C Voltage Range: Rated Voltage±6%					
*We reserve the right t	o make changes in specifications and design without prior notice.					

*We reserve the right to make changes in specifications and design without prior notice.

1. Install the product properly in accordance with the instructions on location, electrical connections stated in the instruction manual provided.

Allow 10mm extra space at the installation site to meet any installation requirements (additional spacing is also required for proper air flow).

pipe connections).

2. The heat rejection is based on the reached pulldown temperature at ambient temperature of 38°C and power supply of 230V 50Hz.

The amperage and electric consumption are based on measurements at ambient temperature of 40°C and power supply of 230V 50Hz.

3. The cabinet temperature range of -2 to 12°C is guaranteed at ambient temperature of 38°C.

4. Product code: T270-W026 (HS)

$C \cap$	APPROV TORIHA	ÆD CH	ecked LIU	DESIGNED ZHOU	DR. Z	AWN HOU	SCALE 1	/30	TRIGON	OMETRY
- ,) (₇	*			*		DATE	7.40.5	DRAWING N	0.	SYMB0L/
\circ	APPROVED	DESIGNED	SYMBOL	DATE		1 2023.12.5		D3/569		/-\