









VIEW A (1/10)



ITEM	Hoshizaki Drawer Type Undercounter Refrigerator
MODEL	RTL-188MA-PD
POWER SUPPLY	1 Phase 230V 60Hz
AMPERAGE	Rated: 2.2A
ELECTRIC CONSUMPTION	Heater: 260W Defrost: 165W
HEAT REJECTION	*W
POWER CORD	2.3m (Plug with Earth Wire)
EFFECTIVE CAPACITY	267L
OUTSIDE DIMENSIONS	1820mm (W) x 750mm (D) x 570 (560-590) mm (H)
INSIDE DIMENSIONS	1300mm (W) x 583mm (D) x 369mm (H)
EXTERIOR	Stainless Steel, Galvanized Steel (Rear/Bottom) Stainless Steel (Door, Front Panel)
INTERIOR	Stainless Steel
INSULATION	Polyurethane Foam
INSULATION FOAM BLOWING AGENT	Cyclopentane
REFRIGERATION SYSTEM	Forced Air Circulation
DEFROST SYSTEM	Heater
COMPRESSOR	-
CONDENSER	Fin and Tube type, Air-cooled
EVAPORATOR	Fin and Tube Type
REFRIGERANT	R134a
TEMPERATURE CONTROL	Microprocessor (Digital Temp Indication) Adjustable from -6 to 12°C
DEFROST CONTROL	Microprocessor
ELECTRIC CIRCUIT PROTECTION	Fuse, Earth Wire
REFRIGERANT CIRCUIT PROTECTION	Motor Protector
LEG	Plastic Adjustable 150 to 180mm
WEIGHT	120kg (Gross Approx. 125kg)
PACKAGE	Carton 1865mm (W) x 830mm (D) x 560mm (H)
ACCESSORIES	Drain Hose x 1, Evaporating Pan x 1
OPERATING CONDITIONS	Ambient Temperature: 5-38°C Voltage Range: Rated Voltage±6%

*We reserve the right to make changes in specifications and design without prior notice.

1. Install the product properly in accordance with the instructions on location, electrical connections stated in the instruction manual provided. Allow 10mm extra space at the installation site to meet any installation requirements (additional spacing is also required for proper air flow and pipe connections).
2. The heat rejection is based on the reached pulldown temperature at ambient temperature of 35°C and power supply of 230V 60Hz. The amperage and electric consumption are based on measurements at ambient temperature of 38°C and power supply of 230V 60Hz.
3. Product code: T253-C300 (For HPH)