


ITEM	Hoshizaki Undercounter Refrigerator
MODEL	RT-158MA-SSG
POWER SUPPLY	1 Phase 220-240V 50Hz Capacity: 0.5kVA (2.5A)
AMPERAGE	Rated 2.4A
ELECTRIC CONSUMPTION	Motor 260W (Power Factor*%) Heater 249W Refrigeration 245W Defrost 165W
HEAT REJECTION	*W
POWER CORD	2.0m (UK Plug with Earth Wire)
EFFECTIVE CAPACITY	420L
OUTSIDE DIMENSIONS	1500mm (W) x 750mm (D) x 850(-880) mm (H)
INSIDE DIMENSIONS	1140mm (W) x 586mm (D) x 599mm (H)
EXTERIOR	Stainless Steel, Galvanized Steel (Rear/Bottom) Double Layer Glass with Heat Reflection Film(Glass Door)
INTERIOR	Stainless Steel
INSULATION	Polyurethane Foam
INSULATION FOAM BLOWING AGENT	Cyclopentane
REFRIGERATION SYSTEM	Forced Air Circulation
DEFROST SYSTEM	Glass Tube Heater
COMPRESSOR	Hermetic
CONDENSER	Wire and Tube type, Air-cooled
EVAPORATOR	Fin and Tube Type
REFRIGERANT	R134a
TEMPERATURE CONTROL	Microprocessor (Digital Temp Indication) Adjustable from -2 to 12°C
DEFROST CONTROL	Microprocessor controlled
ELECTRIC CIRCUIT PROTECTION	Fuse, Earth Wire
COMPRESSOR PROTECTION	Motor Protector
LEG	Plastic Adjustable 150 to 180mm
SHELF	4pcs.
WEIGHT	Net: 105kg (Gross: Approx. 110kg)
PACKAGE	Carton 1565mm (W) x 830mm (D) x 790mm (H)
ACCESSORIES	Drain Hose x 1, Drain Pan x 1
OPERATING CONDITIONS	Ambient Temperature: 5-38°C Voltage Range: Rated Voltage±6%

\*CUSTOMIZED  
SLIDE GLASS DOOR  
LED LAMP

APPROVED TORIHATA		CHECKED ZHOU		DESIGNED ZHOU		DRAWN ZHOU		SCALE 1/20		TRIGONOMETRY	
TORIHATA		ZHOU				2023.11.20		DATE 2023.10.29		DRAWING NO. D37340	
APPROVED		DESIGNED		SYMBOL		DATE				