



ITEM	Hoshizaki Undercounter Freezer
MODEL	FT-158MA-P-ML
POWER SUPPLY	1 Phase 230V 60Hz Capacity: 0.65kVA (2.98A)
AMPERAGE	Rated **A
ELECTRIC CONSUMPTION	Heater 370W Defrost 330W
POWER CORD	2.0m (Plug with Earth Wire)
EFFECTIVE CAPACITY	420L
OUTSIDE DIMENSIONS	1500mm (W) x 750mm (D) x 850(-880) mm (H)
INSIDE DIMENSIONS	1140mm (W) x 586mm (D) x 599mm (H)
EXTERIOR	Stainless Steel, Galvanized Steel (Rear/Bottom) ABS Plastic (Top & Bottom on Door)
INTERIOR	Stainless Steel, ABS Plastic (Door)
INSULATION	Polyurethane Foam
INSULATION FOAM BLOWING AGENT	Cyclopentane
REFRIGERATION SYSTEM	Forced Air Circulation
DEFROST SYSTEM	Glass Tube Heater
COMPRESSOR	Hermetic
CONDENSER	Fin and Tube type, Air-cooled
EVAPORATOR	Fin and Tube Type
REFRIGERANT	R404A
TEMPERATURE CONTROL	Microprocessor controlled Adjustable from -23 to -7℃
DEFROST CONTROL	Microprocessor controlled
ELECTRIC CIRCUIT PROTECTION	Fuse, Earth Wire
COMPRESSOR PROTECTION	Motor Protector
LEG	Plastic Adjustable 150 to 180mm
SHELF	4pcs.
WEIGHT	Net: 89kg (Gross: Approx. 94kg)
PACKAGE	Carton 1565mm (W) x 830mm (D) x 790mm (H)
ACCESSORIES	-
OPERATING CONDITIONS	Ambient Temperature: 5-38℃ Voltage Range: Rated Voltage±6%

4. Product code: T277-C310 (HPH) Unreleased

APPROVED LIANG		CHECKED LIANG		DESIGNED ZHOU		DRAWN ZHOU		SCALE 1/20		TRIGONOMETRY	
##	##		****		DATE 2024.11.01		DRAWING NO. D*****			SYMBOL 	
APPROVED	DESIGNED	SYMBOL	DATE								