










VIEW A(1/10)



ITEM	Hoshizaki Undercounter Freezer/Refrigerator
MODEL	RFT-127MA-P
POWER SUPPLY	1 Phase 230V 60Hz
AMPERAGE	Rated *A
ELECTRIC CONSUMPTION	*W Defrost 495W Heater 535W
POWER CORD	2.0m (Plug with Earth Wire)
EFFECTIVE CAPACITY	Total 261L (Refrigerator:127L Freezer:134L)
OUTSIDE DIMENSIONS	1200mm (W) x 700mm (D) x 850(-880)mm (H)
INSIDE DIMENSIONS	Refrigerator 364mm (W) x 536mm (D) x 599mm (H) Freezer 397mm (W) x 536mm (D) x 599mm (H)
EXTERIOR	Stainless Steel, Galvanized Steel (Rear/Bottom)
INTERIOR	ABS Plastic (Top & Bottom on Door)
INSULATION	Polyurethane Foam
INSULATION FOAM BLOWING AGENT	Cyclopentane
REFRIGERATION SYSTEM	Forced Air Circulation
DEFROST SYSTEM	Glass Tube Heater
COMPRESSOR	Hermetic
CONDENSER	Fin and Tube type, Air-cooled
EVAPORATOR	Fin and Tube Type
REFRIGERANT	R404A
TEMPERATURE CONTROL	Microprocessor (Digital Temp Indication) Adjustable from Refrigerator -3 to 12℃ Freezer -25 to -7℃
DEFROST CONTROL	Microprocessor controlled
ELECTRIC CIRCUIT PROTECTION	Fuse, Earth Wire
COMPRESSOR PROTECTION	Motor Protector
LEG	Plastic Adjustable 150 to 180mm
SHELF	4pcs.
WEIGHT	Net: 84kg (Gross: Approx. 104kg)
PACKAGE	Carton 1265mm (W) x 780mm (D) x 790mm (H)
ACCESSORIES	EVAPORATING PAN KIT
OPERATING CONDITIONS	Ambient Temperature: 5-38℃ Voltage Range: Rated Voltage±6%

*We reserve the right to make changes in specifications and design without prior notice.

1. Install the product properly in accordance with the instructions on location, electrical connections stated in the instruction manual provided.
Allow 10mm extra space at the installation site to meet any installation requirements(additional spacing is also required for proper air flow and pipe connections).

2. Product code: T395-C300(unreleased)