

CERTIFICATION




ICE MATE

by  HOSHIZAKI

SRM-80A ICE MAKER

DICE



ICEMATE is committed to bringing high-efficiency / energy-saving, and high quality ice-making product to people who have dreams and desire to create their own business with the best scientific technology and manufacturing technology.

KEY FEATURES

SAFETY AND HYGIENE ASSURED ICE MACHINE



NSF Certified Material
for Bin and Scoop



Detachable Parts for
Easy Cleaning



Air Filter Prevent Dust
from Entering



Stainless Steel

ENERGY & WATER SAVING, QUIET OPERATION



Energy & Water Saving,
Quiet Operation


EASY MAINTENANCE




IoT




DIMENSIONS




TOP SIDE




FRONT SIDE



RIGHT SIDE



BACK SIDE



SPECIFICATIONS

Ice Dimensions (W x D x H)	22 x 22 x 22 mm	Water Consumption per 24H	(AT32°C/WT21°C) 0.13m ³ (2.3L / kg Ice)
Outside Dimensions (W x D x H)	660 x 670 x 1050 mm	Ice Production Freeze Cycle Time	(AT21°C/WT15°C) 16 min
Package Dimensions (W x D x H)	Carton: 785 x 860 x 1100 mm	Ice Production per Cycle	(AT21°C/WT15°C) Approx. 0.81kg / 80 pcs
Weight (Net / Gross)	56.5 kg / 63 kg	OPERATING CONDITIONS	
Amperage / Starting Amperage	3.2A / 15.0A	Voltage Range	198 - 254 V
Electrical Consumption	(AT32°C / WT21°C) 450 W	Ambient Temperature	5 - 38°C
Refrigerant Charge	R404A / 230g	Water Supply	5 - 32°C
Ice Storage Capacity	Maximum 31.4kg	Water Supply Pressure	0.07 - 0.55 Mpa (0.7 - 5.5 bar)
Ice Production per 24H	(AT10°C / WT10°C) Approx. 80 kg (AT21°C / WT15°C) Approx. 72 kg (AT32°C / WT21°C) Approx. 57 kg	Supply Voltage	1/220 - 240V / 50Hz



HOSHIZAKI

PT. HOSHIZAKI INDONESIA