






SRM-270AB -14-B-501SA

ICE MAKER





ICEMATE is committed to bringing highefficiency / energy-saving, and high quality ice-making product to people who have dreams and desire to create their own business with the best scientific technology and manufacturing technology.

KEY FEATURES

SAFETY AND HYGIENE ASSURED ICE MACHINE

AUTO-CLEANING

Timely maintenance of water system can extend life of equipment.

PURE ICE

Overflow self-cleaning function, ensuring ice hygiene

IoT



Slow melt Dilution

Powerful Ice Making






Energy & Water Saving, Quiet Operation





POWER CORD 2000 LONG OUTSIDE


BIN TOP VIEW



RIGHT SIDE BACK SIDE FRONT SIDE







SPECIFICATIONS

Ice Dimensions (W x D x H)	29 x 14 x 22 mm
Outside Dimensions (W x D x H)	762 x 820 x 1671 (~1701) mm
Package Dimensions (W x D x H)	lce Maker: Pallet+Carton: 850 x 710 x 750mn Storage Bin: 866 x 924 x 1138mm
Weight (Net / Gross)	lce Maker: 59kg / 78kg Storage Bin: 47kg / 57kg
Amperage / Starting Amperage	5.37A/24A
Electrical Consumption	(AT32°C / WT21°C) 1219.5W
Refrigerant Charge	R404A/600g
Ice Storage Capacity	Maximum 217kg
Ice Production per 24H	(AT10°C / WT10°C) Approx. 270 kg (AT21°C / WT15°C) Approx. 229kg (AT32°C / WT21°C) Approx. 183 kg

Water Consumption per 24H	(AT32°C/WT21°C) 0.20m³ (1.1L / kg lce)
Ice Production Freeze Cycle Time	(AT21°C/WT15°C) 15.7 min
Ice Production per Cycle	(AT21°C/WT15°C) Approx. 2.58kg / 320pcs

OPERATING CONDITIONS

Voltage Range	198 - 242 V
Ambient Temperature	5 - 38°C
Water Supply	5 - 32°C
Water Supply Pressure	0.07 - 0.55 Mpa (0.7 - 5.5 bar)
Supply Voltage	1/220 - 240V / 60Hz