

CERTIFICATION





DCM-120LS-P-HC **ICE & WATER DISPENSER**

Key Features



Eco-friendly Refrigerant

HOSHIZAKI





Perfect fit There are no exhaust outlet on the left and right sides and the back, so it can be placed close to the



Easy for maintenance Notify when parts should be replaced



Enhanced daily cleaning routine

Draining board can be removed



No need to hold the bucket with your hands when removing ice

Hoshizaki DCM series are ice/water dispensers producing high-quality servings of cubelet ice and/or water. The three steps of quality ice production, protected ice storage, as well as guick service of ice are all combined in one device - with the help of only one button your refreshment is ready in seconds. With DCM DISPENSERS the user can select from these options:


- Cubelet ice only
- Cubelet ice and water
- Water only


Dimensions & Specifications

ICE SHAPE

CubeletCompressed Flake Ice







MODEL		DCM-120LS-P-HC
ICE SHAPE		Cubelet (Compressed Flake Ice)
POWER SUPPLY		1 Phase 220-240/220-230V 50Hz Capacity: 0.69kVA (3.0A)
AMPERAGE		2.4A Starting: 9.7A
ELECTRIC CONSUMPTION		391W
HEAT REJECTION	(AT32°C / WT21°C)	760W
ICE PRODUCTION PER 24H	(AT10°C / WT10°C)	Approx. 120kg
	(AT21°C / WT15°C)	Approx. 110kg
	(AT32°C / WT21°C)	Approx. 90kg
ICE DISPENSING RATE (40G / CUP)	(AT10°C / WT10°C)	Approx. 225 cups/h
	(AT21°C / WT15°C)	Approx. 214 cups/h
	(AT32°C / WT21°C)	Approx. 193 cups/h
STORAGE CAPACITY		Approx. 4.0kg
WATER CONSUMPTION PER 24H	(AT32°C / WT21°C)	90 L
REFRIGERANT		R290
OUTSIDE DIMENSIONS		Carton: 350mm (W) x 585mm (D) x 815(~830)mm(H)
PACKAGE		Carton: 400mm (W) x 641mm (D) x 872mm(H)
WEIGHT		44kg (Gross: 48kg)
OPERATING CONDITIONS		Ambient Temp.: 5-40°C, Water Supply Temp.: 5-35°C,
		Water Supply Pressure: 0.05-0.78MPa
		Voltage Range: Rated Voltage ±6%



HOSHIZAKI (THAILAND) LIMITED

No. 99 CP Tower North Park building 9th Floor, Zone D1, Soi Ngamwongwan 47 Intersection 42, Thung Song Hong, Subdistrict, Lak Si District, Bangkok 10210 TEL +66 2 005 9980 FAX +66 2 516 2646 https://hoshizaki.co.th/en/

