



HOSHIZAKI

CERTIFICATION



HACCP International



ISO9001



Compliant with IEC60335-2-89 Standard

HR-128MC-S UPRIGHT REFRIGERATOR



Key Features



Lower running cost



Strong cooling power



LED lighting



Drainage-Free Design



Large and clear display



Rounded corner




Removal door gaskets



NATURAL
REFRIGERANTS



Dimensions & Specifications



MODEL	HR-128MC-S
POWER SUPPLY	1 Phase 220-240V 50Hz Capacity: 0.63kVA (2.9A)
ELECTRIC CONSUMPTION	4.34kWh/day
TEMPERATURE CONTROL	-6 to 12°C
STORAGE CAPACITY	1053L
WEIGHT	Net: 132kg (Gross: Approx. 161kg)
OUTSIDE DIMENSIONS	1200mm(W)× 800mm(D)×2050(-2080)mm(H)
PACKAGE	Carton(Woden pallet): 1260mm(W)×900mm(D)×2075mm(H)
NUMBER OF SHELVES	8pcs
REFRIGERANT	R290
OPERATING CONDITIONS	Ambient Temperature: 5 - 38°C, Voltage Range: Rated Voltage ±6%



HOSHIZAKI

HOSHIZAKI MALAYSIA SDN. BHD.

No. 12, Jalan Penyajak U1/45B. Hicom-Glenmarie
Industrial Park, 40150 Shah Alam, Selangor
TEL (+60) 3 5569 8023 <https://hoshizaki.com.my/>

