



HOSHIZAKI

CERTIFICATION



HACCP International




ISO9001

RT-126MA-PG

UNDERCOUNTER SWING GLASS DOOR REFRIGERATOR




Key Features



Forced Evaporation System



LED Interior Lighting




Glass Door with Heater

Our A-fit cabinet combines functionality and excellent energy performance to meet Japan quality level with precise temperature control to ensure food ingredient freshness at all time.



Dimensions & Specifications



MODEL	RT-126MA-PG
POWER SUPPLY	1 Phase 230V 60Hz Capacity: 0.50kVA (2.5A)
ELECTRIC CONSUMPTION	Heater: 229W, Defrost: 165W
TEMPERATURE CONTROL	Microprocessor (Digital Temp. Indication) Adjustable from -2 to 12° C
EFFECTIVE CAPACITY	231L
WEIGHT	Net: 84kg (Gross: Approx. 94kg)
OUTSIDE DIMENSIONS	1200mm(W)× 600mm(D)×850(-880)mm(H)
PACKAGE	Carton: 1265mm(W)×680mm(D)×790mm(H)
AMPERAGE	Rated: 2.3A
SHELF	4 pcs
OPERATING CONDITIONS	Ambient Temperature: 5 - 38°C, Voltage Range: Rated Voltage ±6%



HOSHIZAKI

HOSHIZAKI PHILIPPINES CORPORATION

Unit No. GB-2, G/F Agustin 1 Bldg., # 28 F. Ortigas Center, Pasig City

TEL +632 8839 2861 <https://hoshizaki-sea.com/>

