

CERTIFICATION





ISO9001

RT-128MA-S-PR **UNDERCOUNTER PREP TABLE**



Key Features








Our A-fit cabinet combines functionality and excellent energy performance to meet Japan quality level with precise temperature control to ensure food ingredient freshness at all time.

Dimensions & Specifications



MODEL	RT-128MA-S-PR
POWER SUPPLY	1 Phase 220-240V 50Hz Capacity: 0.6kVA (2.6A)
ELECTRIC CONSUMPTION	Motor: 262W Heater: 78W Refrigeration: 267 Defrost: 78W
TEMPERATURE CONTROL	Microprocessor Adjustible from - 2 to 12°C
EFFECTIVE CAPACITY	304L
WEIGHT	Net: 75kg (Gross: Approx 80kg)
OUTSIDE DIMENSIONS	1200mm(W)× 750mm(D)×850(-880)mm(H)
PACKAGE	Carton: 1265mm(W)×830mm(D)×790mm(H)
AMPERAGE	Rated: 2.1A
SHELF	4 pcs
OPERATING CONDITIONS	Ambient Temperature: 5 - 32°C, Voltage Range: Rated Voltage ±6%



HOSHIZAKI MALAYSIA SDN. BHD.

16, JALAN TP5A, Prestij 16, Taman Perindustrian Uep, 47620 Subang Jaya, Selangor TEL +603-8023 5823 https://hoshizaki.com.my/

