



HOSHIZAKI

CERTIFICATION



HACCP International




ISO9001

RT-156MA-PSG UNDERCOUNTER SLIDING GLASS DOOR REFRIGERATOR



Key Features



**Forced Evaporation
System**




**LED Interior
Lighting**

Our A-fit cabinet combines functionality and excellent energy performance to meet Japan quality level with precise temperature control to ensure food ingredient freshness at all time.



Dimensions & Specifications



MODEL	RT-156MA-PSG
POWER SUPPLY	1 Phase 220-240V 60Hz Capacity: 0.5kVA (2.5A)
ELECTRIC CONSUMPTION	Heater: 249W Defrost: 165W
TEMPERATURE CONTROL	Microprocessor (Digital Temp. Indication) Adjustable from -2 to 12° C
EFFECTIVE CAPACITY	318L
WEIGHT	Net: 97kg (Gross: Approx. 102kg)
OUTSIDE DIMENSIONS	1500mm(W)× 600mm(D)×850(-880)mm(H)
PACKAGE	Carton: 1565mm(W)×680mm(D)×790mm(H)
AMPERAGE	Rated: 2.3A
SHELF	4 pcs
OPERATING CONDITIONS	Ambient Temperature: 5 - 38°C, Voltage Range: Rated Voltage ±6%



HOSHIZAKI

HOSHIZAKI PHILIPPINES CORPORATION

Unit No. GB-2, G/F Agustín 1 Bldg., # 28 F. Ortigas Center, Pasig City, 1605

TEL +632 8839 2861 <https://hoshizaki-sea.com/>

