



HOSHIZAKI

CERTIFICATION



HACCP International




ISO9001

RT-156MA-S-3D UNDERCOUNTER REFRIGERATOR




Key Features



**Forced Evaporation
System**



**LED Interior
Lighting**




**2/3 GN Compatible
Drawers**

(GN Trays are not included)*
*Max. Depth 100mm

Our A-fit cabinet combines functionality and excellent energy performance to meet Japan quality level with precise temperature control to ensure food ingredient freshness at all time.



Dimensions & Specifications



MODEL	RT-156MA-S-3D
POWER SUPPLY	1 Phase 230V 50Hz, Capacity: 0.5kVA (2.5A)
ELECTRIC CONSUMPTION	Motor: 260W, Heater: 189W, Refrigeration: 245W, Defrost: 165W
TEMPERATURE CONTROL	Microprocessor (Digital Temp Indication) Adjustable from -6 to 12°C
EFFECTIVE CAPACITY	318L
WEIGHT	Net: 81kg (Gross: Approx 86kg)
OUTSIDE DIMENSIONS	1500mm (W) x 600mm (D) x 850(-880)mm (H)
PACKAGE	Carton: 1565mm (W) x 680mm (D) x 790mm (H)
AMPERAGE	Rated 2.0A
SHELF	2 pcs
OPERATING CONDITIONS	Ambient Temperature: 5 to 38°C, Voltage Range: Rated Voltage $\pm 6\%$



HOSHIZAKI

HOSHIZAKI SINGAPORE PTE LTD

18 Boon Lay Way #01-102 Tradehub21, Singapore, 609966

TEL 6225 2612 FAX 6225 3219 www.hoshizaki.com.sg

