



HOSHIZAKI

CERTIFICATION



HACCP International



ISO9001

RT-186MA-P UNDERCOUNTER REFRIGERATOR



Key Features



**Forced Evaporation
System**




**LED Interior
Lighting**

Our A-fit cabinet combines functionality and excellent energy performance to meet Japan quality level with precise temperature control to ensure food ingredient freshness at all time.



Dimensions & Specifications



MODEL	RT-186MA-P
POWER SUPPLY	1 Phase 230V 60Hz Capacity: 0.67kVA (3.05A)
ELECTRIC CONSUMPTION	Motor: 270W Heater: 201W Refrigeration: 280W Defrost: 201W
TEMPERATURE CONTROL	Microprocessor (Digital Temp. Indication) Adjustable from -6 to 12°C
EFFECTIVE CAPACITY	401L
WEIGHT	Net: 93kg (Gross: Approx. 98kg)
OUTSIDE DIMENSIONS	1800mm(W)× 600mm(D)×850(-880)mm(H)
PACKAGE	Carton: 1865mm(W)×680mm(D)×790mm(H)
AMPERAGE	Rated: 2.1A
SHELF	3 pcs
OPERATING CONDITIONS	Ambient Temperature: 5 - 43°C, Voltage Range: Rated Voltage ±6%



HOSHIZAKI

HOSHIZAKI PHILIPPINES CORPORATION

Unit No. GB-2, G/F Agustin 1 Bldg., # 28 F. Ortigas Center, Pasig City
 TEL +632 8839 2861 <https://hoshizaki-sea.com/>

