

CERTIFICATION



HACCP International



RT-188MA-S-PR
UNDERCOUNTER PREP TABLE



Key Features








Our A-fit cabinet combines functionality and excellent energy performance to meet Japan quality level with precise temperature control to ensure food ingredient freshness at all time.





Dimensions & Specifications








		1625		325	176
1/3	1/3	1/3	1/3	1/3	1
1/3	1/3	1/3	1/3	1/3	528
1/3	1/3	1/3	1/3	1/3	· •
	GN	PAN LA	YOUT		











MODEL	RT-188MA-S-PR			
POWER SUPPLY	1 Phase 220-240V 50Hz Capacity: 0.78kVA (3.55A)			
ELECTRIC CONSUMPTION	Motor: 380W Heater: 149W Refrigeration: 416 Defrost: 149W			
TEMPERATURE CONTROL	Microprocessor Adjustible from - 2 to 12°C			
EFFECTIVE CAPACITY	517L			
WEIGHT	Net: 108kg (Gross: Approx 113kg)			
OUTSIDE DIMENSIONS	1800mm(W)× 750mm(D)×850(-880)mm(H)			
PACKAGE	Carton: 1865mm(W)×830mm(D)×790mm(H)			
AMPERAGE	Rated: 2.5A			
SHELF	6 pcs			
OPERATING CONDITIONS	Ambient Temperature: 5 - 32°C, Voltage Range: Rated Voltage ±6%			



HOSHIZAKI MALAYSIA SDN. BHD.

16, JALAN TP5A, Prestij 16, Taman Perindustrian Uep, 47620 Subang Jaya, Selangor TEL +603-8023 5823 https://hoshizaki.com.my/

