

CERTIFICATION







RT-96MA-S UNDERCOUNTER REFRIGERATOR




Key Features





Our A-fit cabinet combines functionality and excellent energy performance to meet Japan quality level with precise temperature control to ensure food ingredient freshness at all time.

Dimensions & Specifications



MODEL	RT-96MA-S
POWER SUPPLY	1 Phase 230V 50Hz Capacity: 0.50kVA (2.5A)
ELECTRIC CONSUMPTION	Motor: 220W Heater: 175W Refrigeration: 240W Defrost: 165W
TEMPERATURE CONTROL	Microprocessor (Digital Temp. Indication) Adjustable from -6 to 12°C
EFFECTIVE CAPACITY	151L
WEIGHT	Net: 61kg (Gross: Approx. 65kg)
OUTSIDE DIMENSIONS	900mm(W)× 600mm(D)×850(-880)mm(H)
PACKAGE	Carton: 965mm(W)×680mm(D)×790mm(H)
AMPERAGE	Rated: 2.0A
SHELF	2 pcs
OPERATING CONDITIONS	Ambient Temperature: 5 - 38°C, Voltage Range: Rated Voltage ±6%



HOSHIZAKI MALAYSIA SDN. BHD.

16, JALAN TP5A, Prestij 16,

Taman Perindustrian Uep, 47620 Subang Jaya, Selangor TEL +603-8023 5823 https://hoshizaki.com.my/

