

CERTIFICATION





RT-98MA-P UNDERCOUNTER REFRIGERATOR




Key Features





Our A-fit cabinet combines functionality and excellent energy performance to meet Japan quality level with precise temperature control to ensure food ingredient freshness at all time.

Dimensions & Specifications



MODEL	RT-98MA-P
POWER SUPPLY	1 Phase 230V 60Hz Capacity: 0.5kVA (2.5A)
ELECTRIC CONSUMPTION	Motor: 220W Heater: 175W Refrigeration: 240W Defrost: 175W
TEMPERATURE CONTROL	Microprocessor (Digital Temp. Indication) Adjustable from -6 to 12°C
EFFECTIVE CAPACITY	199L
WEIGHT	Net: 67kg (Gross: Approx. 72kg)
OUTSIDE DIMENSIONS	900mm(W)× 750mm(D)×850(-880)mm(H)
PACKAGE	Carton: 965mm(W)×830mm(D)×790mm(H)
AMPERAGE	Rated: 2.0A
SHELF	2 pcs
OPERATING CONDITIONS	Ambient Temperature: 5 - 43°C, Voltage Range: Rated Voltage ±6%



HOSHIZAKI PHILIPPINES CORPORATION

Unit No. GB-2, G/F Agustin 1 Bldg., # 28 F. Ortigas Center, Pasig City TEL +632 8839 2861 https://hoshizaki-sea.com/

