



HOSHIZAKI

CERTIFICATION



HACCP International




ISO9001

RT-98MA-SG

UNDERCOUNTER SWING GLASS DOOR REFRIGERATOR




Key Features



Forced Evaporation System



LED Interior Lighting




Glass Door with Heater

Our A-fit cabinet combines functionality and excellent energy performance to meet Japan quality level with precise temperature control to ensure food ingredient freshness at all time.



Dimensions & Specifications



MODEL	RT-98MA-SG
POWER SUPPLY	1 Phase 230V 50Hz Capacity: 0.50kVA (2.5A)
ELECTRIC CONSUMPTION	Heater: 201W, Defrost: 165W
TEMPERATURE CONTROL	Microprocessor (Digital Temp. Indication) Adjustable from -2 to 12° C
EFFECTIVE CAPACITY	199L
WEIGHT	Net: 72kg (Gross 77kg)
OUTSIDE DIMENSIONS	900mm(W)× 750mm(D)×850(-880)mm(H)
PACKAGE	Carton: 965mm(W)×830mm(D)×790mm(H)
AMPERAGE	Rated: 2.2A
SHELF	2 pcs
OPERATING CONDITIONS	Ambient Temperature: 5 - 38°C, Voltage Range: Rated Voltage ±6%



HOSHIZAKI

HOSHIZAKI MALAYSIA SDN. BHD.

16, JALAN TP5A, Prestij 16,
Taman Perindustrian Uep, 47620 Subang Jaya, Selangor
TEL +603-8023 5823 <https://hoshizaki.com.my/>

