



# HOSHIZAKI

## CERTIFICATION



HACCP International



ISO9001

## RTL-106MA-SD LOW DRAWER UNDERCOUNTER REFRIGERATOR



### Key Features



**Forced Evaporation  
System**










**2/3 GN Compatible  
Drawers**

(GN Trays are not included)\*  
\*Max. Depth 100mm

Our A-fit cabinet combines functionality and excellent energy performance to meet Japan quality level with precise temperature control to ensure food ingredient freshness at all time.



## Dimensions & Specifications



MODEL	RTL-106MA-SD
POWER SUPPLY	1 Phase 230V 50Hz Capacity: 0.5kVA(2.27A)
ELECTRIC CONSUMPTION	Heater: 238W Defrost: 165W
TEMPERATURE CONTROL	Microprocessor (Digital Temp. Indication) Adjustable from -6 to 12° C
EFFECTIVE CAPACITY	60L
WEIGHT	Net: 67kg (Gross 72kg)
OUTSIDE DIMENSIONS	980mm(W) × 600mm(D) × 570 (560-590) mm(H)
PACKAGE	Carton 1045mm(W) × 680mm(D) × 560mm(H)
AMPERAGE	Rated: 2.2A
OPERATING CONDITIONS	Ambient Temperature: 5 - 38°C, Voltage Range: Rated Voltage ±6%



# HOSHIZAKI

**HOSHIZAKI MALAYSIA SDN. BHD.**

16, JALAN TP5A, Prestij 16,  
Taman Perindustrian Uep, 47620 Subang Jaya, Selangor  
TEL +603-8023 5823 <https://hoshizaki.com.my/>

