



HOSHIZAKI

CERTIFICATION



HACCP International



ISO9001


RTL-108MA-SD LOW DRAWER UNDERCOUNTER REFRIGERATOR



Key Features



**Forced Evaporation
System**










**1/1 GN Compatible
Drawers**

(GN Trays are not included)*
*Max. Depth 100mm

Our A-fit cabinet combines functionality and excellent energy performance to meet Japan quality level with precise temperature control to ensure food ingredient freshness at all time.



Dimensions & Specifications



MODEL	RTL-108MA-SD
POWER SUPPLY	1 Phase 220 - 240V 50Hz Capacity: 0.5kVA(2.27A)
ELECTRIC CONSUMPTION	Motor: 225W Heater: 238W Refrigeration: 304W Defrost: 238W
TEMPERATURE CONTROL	Microprocessor (Digital Temp. Indication) Adjustable from -6 to 12° C
EFFECTIVE CAPACITY	85L
WEIGHT	Net: 67kg (Gross 72kg)
OUTSIDE DIMENSIONS	980mm(W) × 750mm(D) × 570 (560-590) mm(H)
PACKAGE	Carton 1045mm(W) × 830mm(D) × 560mm(H)
AMPERAGE	Rated: 1.9 A
OPERATING CONDITIONS	Ambient Temperature: 5 - 38°C, Voltage Range: Rated Voltage ±6%



HOSHIZAKI

HOSHIZAKI VIETNAM CORPORATION

168/14 Nguyen Gia Tri Street,
Ward 25, Binh Thanh District, Ho Chi Minh City, 760000
TEL +84 0 916 161 346 <https://hoshizaki-sea.com/>

