



HOSHIZAKI

CERTIFICATION



HACCP International



ISO9001



Compliant with IEC60335-2-89 Standard

RT-188MC-S UNDERCOUNTER REFRIGERATOR




Key Features



Lower running cost



Strong cooling power



LED lighting



Drainage-Free Design



Large and clear display



Rounded corner










Removal door gaskets




NATURAL
REFRIGERANTS



Dimensions & Specifications



MODEL	RT-188MC-S
POWER SUPPLY	1 Phase 220-240V 50Hz Capacity: 0.41kVA (1.86A)
ELECTRIC CONSUMPTION	3.43kWh/day
TEMPERATURE CONTROL	-6 to 12°C
STORAGE CAPACITY	502L
WEIGHT	Net: 109kg (Gross: Approx. 121kg)
OUTSIDE DIMENSIONS	1800mm(W)× 750mm(D)×850(-880)mm(H)
PACKAGE	Carton: 1865mm(W)×830mm(D)×845mm(H)
NUMBER OF SHELVES	6pcs
REFRIGERANT	R290
OPERATING CONDITIONS	Ambient Temperature: 5 - 38°C, Voltage Range: Rated Voltage ±6%



HOSHIZAKI

HOSHIZAKI SINGAPORE PTE. LTD.

18 Boon Lay Way #01-102 Tradehub21, 609966

TEL 6225 2612 FAX 6225 3219

www.hoshizaki.com.sg

